

(12) UK Patent Application (19) GB (11) 2 347 055 (13) A

(43) Date of A Publication 23.08.2000

(21) Application No 9907693.7

(22) Date of Filing 01.04.1999

(30) Priority Data

(31) 09251591

(32) 17.02.1999

(33) US

(71) Applicant(s)

3Com Corporation

(Incorporated in USA - Delaware)

5400 Bayfront Plaza, P O Box 58145, Santa Clara,
California 95052-8145, United States of America

(72) Inventor(s)

Jon Jameson Burgess

Thomas C Hogan

(74) Agent and/or Address for Service

Bowles Horton

Felden House, Dower Mews, High Street,
BERKHAMSTED, Herts, HP4 2BL, United Kingdom

(51) INT CL⁷

H04L 12/44 , H04H 1/02

(52) UK CL (Edition R)

H4P PPBC PPNE

U1S S2123 S2202 S2206

(56) Documents Cited

EP 0412220 A1

EP 0292072 A1

(58) Field of Search

UK CL (Edition Q) H4P PPBB PPBC PPC PPNE


INT CL⁶ H03H , H04H , H04L

Online: WPI, JAPIO, EPODOC

(54) Abstract Title

Network connections

(57) A network includes one or more passive communications hub 12 having a number of ports 12a, with the network being made up of connections to, and optionally interconnections between, the ports. The network is arranged to carry electrical signals of different frequencies and characteristics. In particular the network distributes DC signals substantially without attenuation, and oscillation signals substantially without reflection. In the preferred implementation, the network carries both TV signals and computer network signals, such as ethernet signals. In this context the carrying of DC signals substantially without attenuation, by way of a controlled DC resistance in the network, enables the proper functioning of ethernet collision detection.



GB 2 347 055 A